
DN-120



MECHANICAL

Length: 3.25" (82.6 mm) Width: 2.5" (63.5 mm) Height: 1.08" (27.4 mm)

ELECTRICAL

Voltage: 11-28 VDC at 50 mA Loss-of-ground Protection: Yes Reverse Polarity: -30 VDC Signal Levels: ISO 11898 Isolation: 500V ESD Protection: ±10 kv Overload Protection: ±30 V° Short Circuit: Indefinite Output Levels: ±7.9V (typical)

ENVIRONMENTAL

Enclosure: Plastic housing **Operating Temperature:** 0° to 70° C (32° to 158°F)

COMMUNICATION

Interface: RS-232

Protocols: RS-232 to DeviceNet

serial gateway **Data Bits:** 8, 7 (determined by

parity setting)

Parity: Even, odd, none (software

configurable) Stop Bits: 1 (fixed)

Baud Rate: 300, 1200, 2400. 4800, 9600, 19.2K (software/ hardware selected)

Flow Control: None, RTS/CTS,

X-on/X-off

CONNECTORS

Scanner Connector: DB-9 plug

Pin	Function
1	NC
2	Receive data RS-232 (in)
3	Transmit data RS-232 (out)
4	NC
5	Ground
6	NC
7	Request-to-send RS-232 (out)
8	Clear-to-send RS-232 (in)
9	NC

Host Connector: 5-pin MicroChange

Pin	Function
1	Drain
2	Bus +
3	Bus -
4	CAN H
5	CAN L

Interface Box

DeviceNet is a communication protocol managed by the Open DeviceNet Vendors Association (ODVA), with Controller Area Network (CAN) as the backbone technology. The protocol is used in the automation industry as a quick and economical way to network a variety of devices.

The DN-120 Interface Box easily connects any Omron Microscan RS-232 bar code reader to a DeviceNet network. Mac ID and serial channel are rotary switch selectable or software configurable. Other DeviceNet interface box features include a loss-of-ground protection circuit, fully isolated RS-232 serial channel, and selectable serial baud rate (300 to 19.2k).

For more information on this product, visit www.microscan.com.

ISO CERTIFICATION

Certified ISO 9001:2008 Quality Management System

©2018 Omron Microscan Systems, Inc. SP024E-EN-0218 Warranty-For current warranty information on this product, please visit www.microscan.com/warranty

OMRON

MICROSC/MN

Omron Microscan Systems Inc.

Tel 425 226 5700 / 800 251 7711

Fax 425 226 8250

Omron Microscan Europe

Tel 31 172 423360 / Fax 31 172 423366

Omron Microscan Asia Pacific

Tel 65 6846 1214 / Fax 65 6846 4641

www.microscan.com

Product Information: info@microscan.com Technical Support: helpdesk@microscan.com