



## Software CD-ROM

This is a CD-ROM containing software for Sentech USB cameras, included as standard with the product. The package contains demonstration software (viewer software), drivers and documentation. Please let our sales department know if you do not require a CD-ROM, such as when purchasing multiple units or for repeat orders.

Name	Supported Models	Category	Supported OS	Date Updated
StCamUSBPack Ver.3.01	All USB models	Basic Pack	XP SP2 or later/Vista/Win7/Linux	2012/11/6



## Tripod mount

Optional adapter for fastening the camera with tripod screws.

Model No.	Supported Models
TP-HCA	USB2.0, USB3.0 (1.3M, 5M)
TP-JVA	USB3.0 (With SONY 2M,2.3M,3.2M,4M,5M CMOS sensor)



## CS-to-C-Mount Conversion Adapter

Conversion adapter ring required when using a C-mount lens on a CS-mount camera.

Model No.	Supported Models
CS-C-R	CS Mount Model



Sentech has made available a line of optional screw-fastened cables, responding to many requests for such cables when using USB cameras in the FA field.

USB<->USB Mini-B cables used on USB hardware trigger models and mini models.

Model No.	Supported Models	Connector Configuration	Length
CAB-USB-02-MB	Hardware trigger model, mini model	USB Mini-B, with camera-side fastening screws	2m
CAB-USB-03-MB	Hardware trigger model, mini model	USB Mini-B, with camera-side fastening screws	3m
CAB-USB-05-MB	Hardware trigger model, mini model	USB Mini-B, with camera-side fastening screws	5m



Cable with lock screw for USB 3.0 and cable with robot cable specifications are available.

Cable with lock screw for USB 3.0 and cable with robot cable specifications are available.			
Model No.	Supported Models	Connector Configuration	Length
NU3MBASU3S-2m	All USB 3.0 models	USB 3.0 MicroB, with camera-side fastening screws	2m
NU3MBASU3S-3.5m	All USB 3.0 models	USB 3.0 MicroB, with camera-side fastening screws	3.5m
NU3MBASU3S-5m	All USB 3.0 models	USB 3.0 MicroB, with camera-side fastening screws	5m
USB3-KT5-A-MBS-050	All USB 3.0 models	USB3.0 MicroB, with camera-side fastening screws, Robot cables	5m
NU3MBASU3B-2m	All USB 3.0 models	USB 3.0 MicroB, with camera-side fastening screws, high folding cables	2m
NU3MBASU3B-3.5m	All USB 3.0 models	USB 3.0 MicroB, with camera-side fastening screws, robot cables	3.5m
1U30A-MB2-SA1-500	All USB 3.0 models	USB3.0 MicroB, wish camera-side fastening screws	5m
1U30A-MB2-SA1-700	All USB 3.0 models	USB3.0 MicroB, wish camera-side fastening screws	7m
1U30A-MB2-SA1-A00	All USB 3.0 models	USB3.0 MicroB, wish camera-side fastening screws	10m

\* Please make sure that USB 3.0 cables operate correctly under your environment beforehand.



## Lens for USB 2.0 Board Camera

Model No.	Supported Models		Focal Length	F-stop	Angle of view when using a 1/3" CCD		
					Vertical (°)	Horizontal (°)	Diagonal (°)
CV0205C	USB 2.0 Board Camera	SB/SCxxUSB-BLL	f=2.5mm	2.0	85.7	115.7	148
CV0206C			f=4.0mm	2.5	45	83	96
CV0219D			f=6.0mm	2.5	34	46	56

\* The image angle of the CV0206C is the value for the 1/2.7" sensor.