

### Software CD-ROM

This is the CD-ROM containing communications software for Sentech Camera Link cameras. As the CD-ROM is not included as standard with products, customers requiring the software should contact the Sentech sales department.

Name	Supported Models	Category	Supported OS	Date Updated
StCtrl2	All Camera Link	Communications and	XP SP2 or	-
	models	Various Setting Modification Software	later/Vista/Win7	



#### **AC ADAPTER**

This is an AC adapter (optional) to power the camera. Required for models other than PoCL. The adapter supports multiple voltages (100 - 240VAC) and is CE and RoHS compliant.

Model No.	Supported Models	Connector Configuration	IN	OUT
UN310- 6P	Standard Model/New PoE Model	6P connector:HR10A-7P- 6S	100- 240Vac	12V1A



## Tripod mount

Optional adapter for fastening the camera with tripod screws.

Model No.	Supported Models
TP-HCA	CCD Model : MB/MC33,83,133,152,202PCL
TP-HXA	MB/MC232PCL
TP-IDA	CMOS Model : SPB/SPC312,322,500,510



# Lenses for Head Separation Cameras

This is a lineup of small-diameter fixed focal length lenses for the emote head Camera Link camera.

	Supported Models	Focal Length	F-stop	Angle of view when using a 1/3" CCD		
Model No.				Vertical (°)	Horizontal (°)	Diagonal (°)
VL- 3120STM	Remote head model	f=3.1mm	2	70.1	94.8	122.4
LT-6STM	Remote head model	f=6.0mm	2	33.8	45.3	56.9
VH160STM	Remote head model	f=16mm	3.4	12.8	17.1	21.2
VG340STM	Remote head model	f=30mm	3.4	6.9	9.2	11.4



#### Camera Link Cables

Various cables are available. Please contact the Sentech sales department for details.

Model No.	Supported Models	
Camera Link Cables	All Camera Link models	



### Mount converter adapter

Adapter to convert M42 P=1 FB=10 mm for 12M camera to F mount.

Model No.	Supported Models		
M42-F-R	12M		